

# Flagship laser ODL-721

## Laser-lit rear-projection video walls for 24/7 control rooms



Powered with the latest RGB laser technology, Barco's Flagship laser rear-projection video walls delivers unseen brightness levels and vibrant colors, while offering a very low total cost of ownership (TCO). With its 10th generation of rear-projection video walls, Barco again raises the bar for critical infrastructure markets visualization.

Providing 2x more brightness than mainstream LED-lit rear-projection video walls, the Flagship laser series take away all brightness issues of earlier video walls. Because the high luminance allows operating under daylight conditions, control rooms can finally light up - which improves operator working conditions! Adding vibrant colors to this mix, that make all nuances clearly distinguishable, you make sure nothing is wrongly interpreted and situational awareness is enhanced.

### Over 11 years of uninterrupted 24/7 operations

With the Flagship laser for 24/7 control rooms series, Barco takes another giant leap forward in terms of reliability. With a lifetime of at least 100,000 hours in eco-mode, operators enjoy a staggering 11.5 years of uninterrupted 24/7 operations. Redundancy of all critical components (including power supply, inputs, and drivers) make sure nothing is left to chance when it comes to uptime. Unlike laser-phosphor technology used by competitors and in non-24/7 meeting rooms, Barco's Flagship laser display series doesn't need a rotating color wheel to operate. Since each color can be uniquely controlled and is not dependent on the segment of a color wheel, it provides color control like never before and eliminates color breakup.

### Automatic calibration and alignment

The engine of Barco's Flagship laser for 24/7 control rooms is fully motorized. Installers and maintenance staff will never need to open up the individual modules to perfectly align the individual cubes of the video wall. Using a web interface, the video wall can be remotely aligned by a single technician - including keystone correction. This is far more efficient, more reliable, and less time consuming, saving up to 50% of alignment and adjustments efforts. Combined with the Sense X automatic calibration system, continuously measuring and adjusting brightness and color levels over the complete video wall, users are sure the complete canvas is perfectly balanced at any time.

**BARCO**

Visibly yours

## Product specifications

## Flagship laser ODL-721

<b>Resolution</b>	Full HD (1920 x 1080 pixels)					
<b>Screen</b>	<b>Screen type WV-FEL</b>	<b>NoGap</b>	<b>CSI</b>	<b>Engine lifetime (hrs)</b>	<b>Power usage</b>	
	Boost	800 cd/m <sup>2</sup>	680 cd/m <sup>2</sup>	550 cd/m <sup>2</sup>	60,000	260 W
	Normal	620 cd/m <sup>2</sup>	530 cd/m <sup>2</sup>	430 cd/m <sup>2</sup>	80,000	200 W
	Eco	310 cd/m <sup>2</sup>	265 cd/m <sup>2</sup>	215 cd/m <sup>2</sup>	100,000	120 W
	Horizontal half gain viewing angle	38°	36°	36°	-	-
	Vertical half gain viewing angle	21°	33°	34°	-	-
<b>On-screen contrast</b>	1800:1					
<b>Color</b>	Up to 170% EBU color triangle					
<b>Display technology</b>	Rear projection DLP					
<b>White point</b>	Customized white points					
<b>Brightness uniformity</b>	Typ. >95% ANSI 9 Typ. >90% ANSI 13					
<b>Screen gap</b>	Dependant on screen type					
<b>Color stability</b>	Sense X automatic calibration					
<b>Dimensions</b>	<ul style="list-style-type: none"> <li>• Diagonal: 70" (Approx.)</li> <li>• Width: 1,550 mm   61.02"</li> <li>• Height: 872 mm   34.33"</li> <li>• Depth: 622 mm   24.49"</li> <li>• Weight: Projection Module: &lt; 63 kg   139 lbs</li> <li>• Weight: Support frame: &lt; 39 kg   86 lbs</li> </ul>					
<b>Light source</b>	RGB lasers illumination (Lasers Class 2)					
<b>Redundancy</b>	Redundant laser banks with redundant power supply drivers, input signal & external power supply					
<b>Light source lifetime</b>	<ul style="list-style-type: none"> <li>&gt; 100,000hrs in eco mode</li> <li>&gt; 80,000hrs in normal mode</li> <li>&gt; 60,000hrs in boost mode</li> </ul>					
<b>Conditions for operation</b>	10°C-40°C   50°F-104°F Up to 80% humidity (non-condensing)					
<b>AC input voltage</b>	100 – 240 VAC, 50-60Hz					
<b>Power</b>	120W (eco) 200W (normal) 260W (boost)					
<b>Heat dissipation</b>	390 BTU/h (eco) 680 BTU/h (typ) 860 BTU/h (max)					
<b>Signal</b>	Redundant Dual link DVI					
<b>Pixel clock</b>	330 MHz					
<b>Input frequency</b>	24 – 62 Hz & 92 - 120 Hz					
<b>Genlock</b>	49 – 61 Hz ; 92 - 120 Hz					
<b>Minimum frame delay</b>	1 frame in minimum frame delay < 2-3 frames in all other cases at full frame rate					
<b>Signal processing</b>	Loop through Free cropping, free scaling					
<b>Direct ethernet access</b>	Built in web server					
<b>Graphical user interface</b>	All settings and operational parameters					
<b>Integration to third party equipment</b>	WEB service API					
<b>Warranty</b>	2 years					

Last updated: 01 Jun 2016  
 Technical specifications are subject to change without prior notice.  
 Please check [www.barco.com](http://www.barco.com) for the latest information.

**BARCO**

Visibly yours