

OV-715

70" SXGA+ DLP™ projection module



Barco's OV-D2 series integrates cutting edge DLP™ technology into 70" video wall systems that are designed and optimized for use in a 24/7 mission critical environment. The Barco designed projection engine provides a set of unique features, resulting in an unrivaled DLP™ rear projection system with outstanding picture quality, reliability and ease of use.

Superior display quality

- Latest high contrast DLP™ technology
- Brightness, contrast, and large viewing angles tailored to the human eye providing maximum readability
- Vibrant colors
- Sense⁶ technology providing consistently excellent video wall uniformity over time

Reliability and lifetime serviceability

- Engineered for ease of maintenance and serviceability
- Durable components with high reliability from lamp to screen
- Dual redundant lamp offering 100% reliability
- Easy lamp replacement from the rear of the system while system runs
- 100% sealed off optical engine, preventing dust contamination
- Fast Ethernet communication allowing redundant projection access for direct control and configuration
- Barco's Lamp-Lease Program allowing to efficiently control operational costs

Flexibility

- Designed to form video walls of any size, in a linear or curved setup
- Requires minimal installation depth
- Innovative modular concept for easier build up and design

Integrated system

- Barco Wall Control Manager software with central graphical overview of the video wall
- Integrating individual projection modules into a single display

BARCO

Visibly yours

Features of the OV-715 projection modules

Sense⁶

Sense⁶ brings wall uniformity to a next level.

Not only does Sense⁶ increase color and brightness uniformity in the corners of each single projection module, Barco's innovative Sense⁶ technology also keeps all projection modules equal over time and across the entire video wall.

By integrating a patented brightness and color sensor, the video wall's color and brightness is continuously measured and communicated between projection modules. Sense⁶ automatically matches the brightness of full white, full black and all gray levels in between, as well as the colors of all projection modules. The I-lamp recalibrates the color sensor for long-time stability.

Sense⁶ operates unnoticed in the background and requires no operator intervention whatsoever. For instance, Sense⁶ will work during automatic lamp change without special operator actions. The intended video wall content remains unchanged at all times. No special screen calibration patterns are needed.




70" OV-715		HVA	HVM	HVX
	Power	Luminance (cd/m² fL) (1)		
120 W	170 50	335 98	830 242	
132 W	185 54	370 108	910 265	
180 W	245 72	n.a.	n.a.	
Seam size screen mullion	0 mm			
interscreen gap	< 0.2 mm by patented stitch concept			
	< 1.5 mm for optimal modular screen (2)			
Humidity conditions	Up to 90% non condensing (2)			
Temperature conditions	12°C-32°C 53.6°F-89.6°F (2)			
Storing conditions	0°C-40°C 32°F-105°F			

(1) @ 6500 K, values are approx 50% @ 3200 K

(2) Depending on wall configuration


(3) @ 25°C, 50% RH

Screens	Screen type	Brightness	Viewing angle	Full viewing angle	Half gain angle (h. v.)	1/5 gain angle (h. v.)
	HVA	Normal	Excellent	180°	±35° ±35°	~ ±65° ±65°
HVM	Medium	Wide	180°	±35° ±27°	~ ±45° ±41°	
HVX	High	Medium	160°	±35° ±10°	~ ±45° ±17°	



ΔE^* is a parameter which incorporates color and brightness differences into one unit. Additionally, ΔE^* takes into account the adaptation level of the human eye to brightness and color.

Sense⁶	Sense⁶ (Optional)	
	Color shift between projection modules over time	Shift in ΔE^* over time < 3 (with color lock)
	On-screen brightness uniformity	Very high brightness and color uniformity
	ANSI 9 brightness min.	97%
	ANSI 13 brightness typ.	95%
	Projector color/brightness uniformity	
	ΔE^* intercube typ.	< 6
	ΔE^* intracube typ.	< 3
	Brightness locking	Makes brightness of all projection modules equal at all times without operator intervention High Dynamic Range (HDR) by optical dimming preserves contrast, independent of brightness level or lamp life Active dynamic brightness sensor feedback technology measures brightness and serves as input to the optical dimmer
	Color locking	Makes color of all projection modules equal at all times without operator intervention Primary Color Adjust is a color algorithm that adjusts color to a common color target in red, green, blue and white Active dynamic color sensor feedback technology collects color information from all projection modules. The True Color Sensor measures the complete spectrum rather than just red, green and blue and is based upon the standard spectral function according to CIE 1931
	Gray locking	Makes gray levels equal across projection modules



Dimensions	OV-715	
	Width W	1400 mm 55.1"
	Height H	1050 mm 41.3"
	Diagonal R	70" nominal
	D1	763 mm 30"
	Full depth D2	899 mm 35.4"
	Aspect ratio	4:3
	Standard height SH	875 mm, 1000 mm, 1200 mm 34.5", 39.4", 47.2"
	Min screen height SH	570 mm ± 30 mm 22.4"
	Weight/module	101.5 kg 224 lbs

Technical specifications OV-715

Display capabilities	Resolution	SXGA+ 1400 x 1050 TruePixel			
	Absolute resolution	25.4 dpi			
	Luminous flux @ 6500 K @ 132 W	1000			
	Dynamic contrast	5100:1			
	Color	100% EBU			
	White point	6500 K, natural lighting (¹)			
	Imaging device	DMD-chip	0.95" LVDS ±12° DarkChip3, BrilliantColor™		
Pixel accuracy		PixelTrue display, shows each pixel true to the input pixels without scaling or smoothing effects			
MTBF of DMD		typ. 650,000 hours			
Lifetime of DMD		typ. > 100,000 hours			
Image retention		No image retention or burn-in			
Lamps		Lamps	Choice between 120 W, 132 W and 180 W		
		Lamp life (²)	120 W	132 W	180 W
		10,000 hrs	6,000 hrs	6,000 hrs	
	Lamp redundancy	Cold standby or hot standby with redundant power supply Automatic lamp switch by autosensing lamp failure			
	Lamp replacement	Defect lamp can be hot-swapped without image loss			
	Lamp switch	Dynamic feedback of brightness and color readjusts video wall to equal performance			
	Switching time	< 1.5 seconds			
	I-lamp	Intelligent lamp carries a.o. lamp life information & spectrum			
	Color wheel	Color wheel, rotation speed & lifetime	Color wheel cartridge with MTTR < 5 minutes		
			3x speed for better image representation		
		Air bearing with rating of 50,000 hours			

Power	AC input voltage	100-240 VAC, 60-50 Hz			
	Power (W)	120 W	132 W	180 W	
	Cold standby	< 250	< 275	< 335	
	Hot standby	< 390	< 430	< 550	
	Heat dissipation (BTU/h)	120 W	132 W	180 W	
Signal	Cold standby	< 850	< 900	< 1145	
	Hot standby	< 1325	< 1375	< 1875	
	Signal input/output	1 x DVI-D in/out, 1 x Dual-link DVI-D in/out			
	Pixel clock	162 MHz 270 MHz (³)			
	Input frequency	Multi sync 30-75 Hz			
	Genlock range	Genlock in 49-61 Hz range			
	Supported input resolutions	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, 1080p, dual XGA, triple XGA (³), quad XGA (³), dual SXGA+(³)			
	Cropping	Possible			
	Scaling (optional)	Up- and down scaling			
	Communications	Barco Wall Control Manager	Graphical representation of video wall on operator PC		
			Integrates separate projection modules into a single display, allowing a.o. Sense⁶		
			Client – server architecture provides central video wall logic with multiple access from multiple sites		
			Health status in the blink of an eye and support for trouble shooting		
			Configuration of different settings		
			Wall control by the operator		
			Multiple access levels		
		Direct ethernet access	Projection module settings and control through standard ethernet browser		
			Easy and fast firmware upgrade over ethernet		
		Autodiagnosics	Projector self test		
	Integration to third party equipment	External video wall control from different devices through SOAP based API			

(¹) Special 3200 K option for backdrop • (²) Lamp manufacturer specs @ IEC 61947-1 test conditions
(³) On second input

Ref. no. R599138SSE0708R003

Barco is an ISO 9001 registered company. The information and data given are typical for the equipment described. However any individual item is subject to change without any notice. The latest version of this product sheet can be found on www.barco.com
DLP™ Technology by Texas Instruments offers crystal clear images with superior quality. DLP, Brilliant Color are trademarks of Texas Instruments.



Contact Barco
Europe, Middle-East, Africa: +32 56 26 20 09
USA: +1 678 475 8000
Latin America: +55 11 38421656
Japan: +81 3 5762 8727
China: +86 400 88 22726
sales.security_and_monitoring@barco.com

BARCO